

## TRANSMITTERS

Surface mounting transmitter  
433,92 Mhz Rolling code



# APPLE



- Transmitter with surface mounting holder
- 433,92Mhz rolling code system, extremely reliable with over 18 billion code combinations
  - Over 100mt range in open-area
  - Battery power supply 12 Vdc
- 2 or 4 channels to control different automations or lamps
- Compatible with all the 433,92Mhz rolling code transmitters

## TRANSMITTERS

433,92 Mhz rolling-code



### APPLE.2

433.92 Mhz self-learning rolling code transmitter available with 2 channels, with surface mounting holder

### APPLE.4

433.92 Mhz self-learning rolling code transmitter available with 4 channels, with surface mounting holder



## RECEIVERS AND ACCESSORIES



### ONE.2WB

433,92 Mhz universal receiver, 2 box channels. Capable of managing three different types of coding: rolling code, programmable code and advanced rolling code. It picks up the coding after the first contact with the One transmitter.



### ONE.2WI

433,92 Mhz universal receiver, 2 plug in channels. Capable of managing three different types of coding: rolling code, programmable code and advanced rolling code. It picks up the coding after the first contact with the One transmitter.




### RR.4WBV RR.4WBV24

433,92Mhz 4-channels receiver rolling code. It is programmable through digital display. 230 Vac power supply mod. RR.4WBV and 24 Vac/dc mod. RR.4WBV24. Advantage system compatible. It works also by battery 12V/dc with self-rechargeable circuit. Max. 4 relais output up to 6A



### CALL

Four-channel GSM receiver, up to 4 automations control, without limits of distance. Makes it possible to use the device by means of a mobile telephone. All characteristics on page 188



### MEM2048

Accessory that allows the extension of the receiver memory up to 2048 codes. For rolling code receiver



### BT12

12 V Battery, for transmitter, available in 50 pcs packing



### AW

433,92Mhz aerial with 5mts cable.